

SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436

444

ACRYLIC/LATEX FLAT FINISH

DESCRIPTION

444 is a good quality maintenance acrylic latex exterior/interior flat finish. 444 has good color retention and acceptance. Ideal for use on properly prepared concrete tilt-up, masonry and stucco.

COLORS

White, black, and bases can be tinted to any colors desired. Can also be manufactured in any color at factory in minimum of 100 gal batches.

PRIMERS/SEALERS

Recommended **SCOTCH COATINGS** primers will vary depending on surface. Check with your local SCOTCH COATINGS DEALER for their expert recommendations.

PACKAGING

5 gallon pails

FINISH

Flat Finish

SUBSTRATES

Stucco, Plaster, Masonry, Concrete, Tilt-up, Drywall, Acoustic and properly prepared wood, and metal.

DRYING TIME

Occasionally, to touch – 1-2 hours
to recoat – 4 to 5 hours

COVERAGE

350 to 450 sq. ft. per gallon depending on surface texture and porosity of surface.

SOLIDS:

By volume 33.07%

SURFACE PREPARATION

All surfaces must be cured, clean and free of loose paint, dirt, dust, rust stains, grease, oil, mildew, wax, efflorescence or any other contaminants. Glossy surfaces must be dulled by sanding

APPLICATION

Airless or conventional spray, brush or roll. Avoid painting in fog, mist, rain, or if the air or surface temperature is below 55°.

CAUTION:

Observe ordinary precautions when using this product. Wash hands before eating or smoking. Avoid breathing vapors or spray mist. Avoid prolonged contact with skin. Use only with adequate ventilation. **DO NOT TAKE INTERNALLY!** **KEEP FROM FREEZING!** **KEEP OUT OF REACH OF CHILDREN!**

VOC

Maximum of 50 grams/liter.

THINNING

Small amount of Water if required.

CLEAN-UP Soap and warm water clean up.

SCOTCH PAINT CORPORATION
555 W. 189TH STREET
GARDENA, CA. 90248