

Scotch Paint Corporation

• *Paint Manufacturers and Distributors of Lacquers, Spray Equipment and Sundries* •

CORPORATE: 1-800-404-2878

555 West 189th Street

Gardena, California 90248

FAX: 1-310-769-0436

PRODUCT NO. 495

ACRI-GLOSS

An interior, exterior premium quality 100% acrylic gloss enamel. Low odor non yellowing formulation possesses excellent hide, adhesion, alkali resistance and color retention for years of outstanding performance.

• RECOMMENDED USES:

Drywall • Wood • Masonry • Concrete
Hardboard • Primed Metal • Stucco

• CHARACTERISTICS:

FINISH: Gloss
DRYING TIME: 1-2 Hrs
SPREADING RATE: 350-400 Sq. feet per gallon
VOLUME SOLIDS: 35.00%
WEIGHT SOLIDS: 46.43%
WEIGHT / GALLON: 10.08
HEAT RESISTANCE: N / A
VEHICLE TYPE: 100% Acrylic
FLASH POINT: N / A
VISCOSITY: 95 KU
V.O.C.: Less than 250 grams per liter

• SURFACE PREPARATIONS:

Be sure all surfaces are dry, smooth and free from dirt, grease, wax, and loose chalking paint. Fill nail holes and cracks with spackling paste or putty. Always clean off all contamination between coats before applying subsequent coats. If surface to be coated is slick or shiny use sandpaper or liquid reglossing compound to remove the shine. Wipe thoroughly to be sure the surface is clean.

• APPLICATION:

Use brush, roller, or spray equipment. Avoid painting in fog, mist, rain, or if the temperature is below 50° F.

• THINNING:

Not required. If thinning is desirable due to weather conditions, a small amount of water may be used.

• CAUTION:

Observe ordinary precautions when using this product. Wash hands before eating or smoking. Avoid breathing vapors or spray mist and prolonged contact with skin. Use only with adequate ventilation. **DO NOT TAKE INTERNALLY, KEEP FROM FREEZING AND KEEP OUT OF REACH OF CHILDREN.**