

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ACRYLIC LATEX EXT. FLAT 50 VOC
PRODUCT CODE: CASX-444

HMIS CODES: H F R P
1 0 0 X

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: Scotch Paint
ADDRESS: 555 WEST 189TH STREET, GARDENA, CALIFORNIA 90248
EMERGENCY PHONE: 310-329-1259 **INFORMATION PHONE:** 310-329-1259
DATE REVISED : 01-01-10 **NAME OF PREPARER :** RJN

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
		OSHA PEL	ACGIH TLV	OTHER		
PROPLYENE GLYCOL	57-55-6	N/A	N/A	N/A	N/A	< 0.5%
SILICON DIOXIDE/AMORPHOUS, MICROCRYSTALLINE SILICA	14808-60-7	0.1Mg/M3	0.1Mg/M3	N/A	N/A	< 0.5%
2,2,4-TRIMETHYLPENTANEDIOL-1,3-MONOISOBUTYRATE	25265-77-4	NE	NE	NE	1.0 189F	< 5.0%

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***
FOLLOW ALL LABEL DIRECTIONS. WARNING THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND
/OR BIRTH DEFECTS OR REPRODUCTIVE HARM. COMPLIES WITH TITLE 8 CALIFORNIA CODE OF REGULATIONS SECTION 5194.

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING RANGE: 369 to 471 Deg F **SPECIFIC GRAVITY (H2O=1):** 1.4
VAPOR DENSITY: HEAVIER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER
COATING V.O.C. : 0.40 LB/GL (48 G/L)
SOLUBILITY IN WATER: VEHICLE PORTION COMPLETE
APPEARANCE AND ODOR: SLIGHT AMMONIA

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT: N/A **METHOD USED:** N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.6% **UPPER:** 12.5%

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

SELF CONTAINED BREATHING APPARATUS RECOMENDED. COMBUSTION PRODUCES CO, CO2

UNUSUAL FIRE AND EXPLOSION HAZARDS

UNKNOWN

=====
SECTION V - REACTIVITY DATA
=====**STABILITY: STABLE
CONDITIONS TO AVOID**

EXCESS HEAT, STRONG ACIDS OR ALKALIS

INCOMPATIBILITY (MATERIALS TO AVOID)

UNKNOWN

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

CO, CO2 ON COMBUSTION

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR=====
SECTION VI - HEALTH HAZARD DATA
=====**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

NAUSEA, DIZZINESS, DROUSINESS, WEAKNESS, HEADACHE.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RASH, BURNING, SWELLING, ITCHING, WATERING EYES.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RASH, SWELLING, ITCHING, REDNESS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NAUSEA, CRAMPS, HEADACHE

HEALTH HAZARDS (ACUTE AND CHRONIC)

UNKNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

UNKNOWN

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

UNKNOWN

EMERGENCY AND FIRST AID PROCEDURES

INHALATION REMOVE TO FRESH AIR. IF UNCONSCIOUS CALL PHYSICIAN IMMEDIATELY.

INGESTION DO NOT INDUCE VOMITING CALL PH

YSICIAN IMMEDIATELY.

SKIN CONTACT WASH WELL WITH SOAP AND WATER. IF RASH DEVELOPES CONSULT PHYSICIAN

EYE CONTACT FLUSH WITH COPIOUS AMOUNT OF WATER CONSULT PHYSICIAN.

=====
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
=====**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

WIPE UP SMALL SPILLS WITH ABSORBANT RAGS OR TOWELS. LARGE SPILLS DIKE AREA AND PUMP INTO DRUMS FOR RECOVERY OR DISPOSAL

WASTE DISPOSAL METHOD

FOLLOW FEDERAL STATE AND LOCAL REGULATIONS REGARDING PROPER DISPOSAL OF PAINT AND RELATED MATERIALS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

WEAR APPROVED ORGANIC VAPOR RESPIRATOR UNLESS ADEQUATE VENTILATION EQUIPMENT IS AVAILABLE TO KEEP ORGANIC VAPOR BELOW TLV

OTHER PRECAUTIONSKEEP CONTAINERS CLOSED WHEN NOT IN USE KEEP FROM OPEN FLAMES OR EXCESS HEAT STORE IN COOL DRY PLACES. DO NOT FREEZE
KEEP OUT OF REACH OF CHILDREN=====
SECTION VIII - CONTROL MEASURES
=====**RESPIRATORY PROTECTION**

WEAR APPROVED RESPIRATOR FOR DUST AND ORGANIC VAPORS.

VENTILATIONOPEN WINDOWS AND DOORS GENERALLY ARE SUFFICIENT TO KEEP TLV BELOW HAZARDOUS CONCENTRATIONS IF NOT EMPLOY MECHANICAL
VENTILATION EQUIPMENT TO KEEP BELOW TLV OF PRODUCT**PROTECTIVE GLOVES**

USE NEOPRENE RUBBER GLOVES TO PROTECT AGAINST SKIN EXPOSURE

EYE PROTECTION

WEAR SPLASH RESISTANT GOGGLES TO PROTECT EYES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NEOPRENE RUBBER APRON RECOMMENDED WHEN USING THIS PRODUCT. WEAR HAT TO PROTECT SCALP FROM THIS PRODUCT.

WORK/HYGIENIC PRACTICES

EMERGENCY EYE WASH AND SAFETY SHOWERS RECOMMENDED. WASH HANDS BEFORE EATING OR SMOKING.

=====
SECTION IX - DISCLAIMER
=====**DISCLAIMER**THE INFORMATION CONTAINED HEREIN IS FURNISHED WITHOUT WARRANTY OF ANY KIND INFORMATION FURNISHED IS BELIEVED TO BE
CORRECT. ANY USE OF THIS INFORMATION MUST BE VERIFIED BY INDEPENDENT DETERMINATION OF SUITABILITY AND COMPLETENESS.