

# SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436



## 325-C ORIGINAL CLEAR

### PENETRATING SEALER/PRIMER

**DESCRIPTION** DRAW TITE penetrating sealer/primer is a remarkable achievement in water based technology. It is superb for sealing ripped, shredded and gouged drywall prior to the application of wall repair compounds. DRAW TITE exhibits excellent moisture resistance and will not bubble or rewet once dry. DRAW TITE is also an excellent choice for sealing chalky porous surfaces. The low odor and non-flammability make this product an excellent substitution for Shellac and oil base primers. DRAW TITE is available in Clear 325C, White 325W, No-Run Clear 325NR. DRAW TITE CLEAR is also available in our new "ZERO V.O. C. GREEN PLANET" formulation. Depending on your job requirements, ask your expert dealer for the DRAW TITE product that is right for your job.

#### **COLOR**

Clear- (Milky White When Wet)

#### **PACKAGING**

Quarts, gallons, and 5 gallon pails

#### **FINISH**

Semi-Gloss

#### **SUBSTRATES**

Sealer/ Primer for damaged or torn drywall, decaying plaster, stucco, or masonry prior to repair.

#### **DRYING TIME**

4 hours. Top coat with mud or repair compounds, and let dry. Reapply selected Draw-Tite product over repaired surfaces prior to applying paint or wall coverings.

#### **COVERAGE**

400-600 Sq. Ft. per gallon, depending on porosity and texture of surface.

#### **SURFACE PREPARATION**

All surfaces must be free of, grease, oil, loose or peeling paint and any foreign material. Remove obvious loose pieces of drywall surface paper.

#### **APPLICATION**

Airless or conventional spray, brush or roll.

#### **FINISHES**

Recommended **SCOTCH COATINGS** Finishes will vary depending on surface and desired finish. Check with your SCOTCH COATINGS DEALER for their expert recommendations. For use under all types of wall treatments, including wallpaper and Venetian plasters. Ideal choice as a sizing on walls in good condition before wallpaper is installed.

#### **CAUTION**

Avoid breathing of vapors or spray mist and prolonged contact with skin. Use with adequate ventilation.

#### **WARNING**

This product contains chemicals known to the state of California to cause cancer and/or birth defects or reproductive harm.

#### **V.O.C.**

The maximum V.O.C. of this product is **ZERO** grams per liter.

#### **THINNING**

Ready to use. DO NOT THIN.

**CLEAN-UP** Soap and warm water clean up immediately after using.

**SCOTCH PAINT CORPORATION**

555 W. 189<sup>TH</sup> STREET  
GARDENA, CA. 90248


# SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436

## 325-C ORIGINAL CLEAR

### PENETRATING SEALER/PRIMER



**DRAW TITE 325-C** clear penetrating sealer/primer is a remarkable achievement in water based technology. It is superb for sealing ripped, shredded and gouged drywall prior to the application of wall repair compounds. DRAW TITE exhibits excellent moisture resistance and will not bubble or rewet once dry. DRAW TITE is also an excellent choice for sealing chalky porous surfaces. The low odor and non-flammability make this product an excellent substitution for Shellac and oil base primers. DRAW TITE is available in Clear 325C, White 325W, No-Run Clear 325NR. DRAW TITE CLEAR is also available in our new "ZERO V.O.C. GREEN PLANET" formulation. Depending on your job requirements, ask your expert dealer for the DRAW TITE product that is right for your job.

### OUTSTANDING FEATURES:

- Seals Damaged Drywall Prior To Applying Wall Repair Compounds
- Works Excellent Under Hot Mud
- Use Over Flat And Enamels To Insure Moisture Resistance
- Can Be Applied Over A Wide Range Of Surfaces, Including Gloss Enamel And Vinyl Wallpaper
- Will Not Lift When Double Cutting Vinyl Wall Coverings
- Promotes Strippability Of Wall Coverings
- Low Odor, Soap and Warm Water Clean- Up

**SURFACE PREPARATION:** All surfaces must be free of, grease, oil, loose or peeling paint and any foreign material. Remove obvious loose pieces of drywall surface paper.

**APPLICATION:** Brush, roller or spray. Apply a generous coat.

**DRYING TIME:** 4 hours. Top coat with mud or repair compounds, and let dry. Reapply selected Draw-Tite product over repaired surfaces prior to applying paint or wall coverings.

**THINNING:** Ready to use. DO NOT THIN.


**COVERAGE** 400-600 Sq. Ft. per gallon, depending on porosity and texture of surface.

**CLEAN-UP:** Soap and warm water.

**IMPORTANT:** Do not apply if surface or air temperature is under 55<sup>0</sup> F.

**KEEP FROM FREEZING  
DO NOT USE IF FREEZING OCCURS  
KEEP OUT OF REACH OF CHILDREN  
CLOSE CONTAINER AFTER EACH USE  
DO NOT TAKE INTERNALLY**

## DRAW TITE FAMILY OF PRODUCTS



SCOTCH PAINT CORPORATION

555 W. 189<sup>TH</sup> STREET

800-404-2878