

SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436



325-CG

CLEAR GREEN ZERO V.O.C. PENETRATING SEALER/PRIMER

DESCRIPTION GREEN CLEAR is formulated with the environment in mind; Green Clear contains ZERO V.O.C. (Volatile Organic Compounds), and is solvent free. Green Clear is a penetrating sealer/primer and is a remarkable achievement in water based technology. It is excellent for sealing ripped, shredded and gouged drywall prior to application of drywall mud or wall repair compounds. It is also ideal for sealing chalky latex builders flat. This extremely low odor non-flammable primer/sealer is an excellent alternative for smelly shellac or alkyd based products. Draw-Tite Clear Green is the latest addition to the Draw-Tite family of products. Just like our other Draw-Tite products, Clear Green has gone through extensive testing both in the lab and in the field, this insures you the best quality Zero V.O.C. product of it's type on the market today. Draw-Tite Green Clear is ideal as a primer sizer, under on walls in good condition as well.

COLOR

Clear- (Milky White When Wet)

PACKAGING

Quarts, gallons, and 5 gallon pails

FINISH

Semi-Gloss

SUBSTRATES

Sealer/ Primer for damaged or torn drywall, decaying plaster, stucco, or masonry prior to repair.

DRYING TIME

4 hours. Top coat with mud or repair compounds, and let dry. Reapply selected Draw-Tite product over repaired surfaces prior to applying paint or wall coverings.

COVERAGE

400-600 Sq. Ft. per gallon, depending on porosity and texture of surface.

SURFACE PREPARATION

All surfaces must be free of, grease, oil, loose or peeling paint and any foreign material. Remove obvious loose pieces of drywall surface paper.

APPLICATION

Airless or conventional spray, brush or roll.

FINISHES

Recommended **SCOTCH COATINGS** Finishes will vary depending on surface and desired finish. Check with your SCOTCH COATINGS DEALER for their expert recommendations. For use under all types of wall treatments, including wallpaper and Venetian plasters. Ideal choice as a sizing on walls in good condition before wallpaper is installed.

CAUTION

Avoid breathing of vapors or spray mist and prolonged contact with skin. Use with adequate ventilation.

WARNING

This product contains chemicals known to the state of California to cause cancer and/or birth defects or reproductive harm.

V.O.C.

The maximum V.O.C. of this product is **ZERO** grams per liter.

THINNING

Ready to use. DO NOT THIN.

CLEAN-UP Soap and warm water clean up immediately after using.

SCOTCH PAINT CORPORATION

555 W. 189TH STREET
GARDENA, CA. 90248

GREEN CLEAR is formulated with the environment in mind; Green Clear contains ZERO V.O.C. (Volatile Organic Compounds), and is solvent free. Green Clear is a penetrating sealer/primer and is a remarkable achievement in water based technology. It is excellent for sealing ripped, shredded and gouged drywall prior to application of drywall mud or wall repair compounds. It is also ideal for sealing chalky latex builders flat. This extremely low odor non-flammable primer/sealer is an excellent alternative for smelly shellac or alkyd based products. Draw-Tite Clear Green is the latest addition to the Draw-Tite family of products. Just like our other Draw-Tite products, Clear Green has gone through extensive testing both in the lab and in the field, this insures you the best quality Zero V.O.C. product of it's type on the market today. Draw-Tite Green Clear is ideal as a primer sizer, under on walls in good condition as well.

OUTSTANDING FEATURES:

- Seals damaged drywall before and after mudding
- Works well under hot mud
- Seals chalky porous latex builders flat
- Extremely low odor
- Zero V.O.C.
- Easy application
- Soap & water clean-up

CAUTION! Avoid breathing of vapors or spray mist and prolonged contact with skin. Use with adequate ventilation.

WARNING: This product contains chemicals known to the state of California to cause cancer and/or birth defects or reproductive harm.

The maximum V.O.C. of this product is **ZERO** grams per liter.

SURFACE PREPARATION: All surfaces must be free of, grease, oil, loose or peeling paint and any foreign material. Remove obvious loose pieces of drywall surface paper.

APPLICATION: Brush, roller or spray. Apply a generous coat.

DRYING TIME: 4 hours. Top coat with mud or repair compounds, and let dry. Reapply selected Draw-Tite product over repaired surfaces prior to applying paint or wall coverings.

THINNING: Ready to use. DO NOT THIN.

COVERAGE 400-600 Sq. Ft. per gallon, depending on porosity and texture of surface.

CLEAN-UP: Soap and warm water.

IMPORTANT: Do not apply if surface or air temperature is under 55^o F.

**KEEP FROM FREEZING
DO NOT USE IF FREEZING OCCURS
KEEP OUT OF REACH OF CHILDREN
CLOSE CONTAINER AFTER EACH USE
DO NOT TAKE INTERNALLY**