

# SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436



## 7000 ACRY-SHEEN 100% Acrylic Semi-Gloss Enamel

### DESCRIPTION

7000 ACRY-SHEEN is quality semi-gloss enamel made with 100% acrylic resin. It has good durability on both exterior and interior surfaces. Use it on exterior sash & trim as well as kitchen and bathroom walls and cabinets and trim through out the home. Equally suitable for schools, hospitals and public buildings needing a durable semi-gloss finish. 7000 can also be manufactured special order as a ZERO V.O.C. coating.

### COLORS

White, Stock colors and Tints

### PACKAGING

Quarts, gallons, 5 gallon pails

### FINISH

Semi-Gloss

Sheen 50 @ 60 degrees

### SUBSTRATES

Properly primed wood, metal, and masonry.

### DRYING TIME

Occasionally, to touch - 1 hour  
to recoat - 8 hours

### COVERAGE

350 to 450 sq. ft. per gallon

### SOLIDS

By volume 37.04%

### SURFACE PREPARATION

All surfaces must be clean and dry and free of dust, loose paint, and surface contaminants that may impair adhesion.

V.O.C. Does not exceed 50 grams/liter

### APPLICATION

Airless or conventional spray, brush or roll.

### PRIMER

BLOCK =  
DRYWALL =

TILT-UP or  
BRICK =

WOOD,NEW =

PREVIOUSLY PAINTED =

METAL:  
FERROUS =

NON-FERROUS =

#S105 Block Filler  
#PV101 PVA Sealer  
#7509 "F" Stop  
#95 Busan Acrylic Primer  
#330 Draw-Tite Primer  
#95 Busan Primer  
#63 Dynacoat Enamel Undercoat  
(Interior only)  
#300 Bus-Stop 100% Acrylic Primer  
#97 100% Acrylic Primer  
  
#902 Red Oxide Primer  
#905 Gray Primer  
  
#95 Busan Primer or  
#908 Zinc Phosphate  
#300 Bus-Stop 100% Acrylic Primer  
#97 100% Acrylic Prime

### THINNING

Small amount of Water if required.

**CLEAN-UP** Soap and warm water clean up.  
(a rinse with lacquer thinner or brush cleaner may be necessary)

**SCOTCH PAINT CORPORATION**  
555 W. 189<sup>TH</sup> STREET  
GARDENA, CA. 90248