

# SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436



## 900 ACRILOX 100% Acrylic Floor Paint

### DESCRIPTION

Scotch Acrilox is a superior 100% Acrylic floor paint for use on exterior and interior surfaces. Acrilox is an ideal product for concrete, masonry and properly prepared wood and metal surfaces. A non-skid additive may be added to this product for better traction.

### COLORS

White, Stock Colors.

Full Color Spectrum of Tints Available From Your Dealer.

### PACKAGING

Quarts, gallons, (and 5 gallon pails on selected stock colors and bases)

### FINISH

Low-Luster

### SUBSTRATES

Properly prepared concrete, masonry, wood, and metal.

### COVERAGE

250 to 450 sq. ft. per gallon, depending on porosity and texture of surface. If non-skid additive is mixed in, this will lessen your coverage per sq. ft.

### SURFACE PREPARATION

All surfaces must be clean and dry and free of dust, loose paint, and surface contaminants that may impair adhesion. New concrete should cure for a minimum of 60 days prior to painting. Smooth or slick concrete should be acid etched, rinsed and thoroughly dry to insure best adhesion.

### APPLICATION

Airless or conventional spray, brush or roll. Apply two thin coats rather than one heavy coat. For best results do not apply to damp surfaces

### DRYING TIME

1 Hour to touch

2 Hours recoat

Light foot traffic after 8 Hours

Let cure 24 to 36 Hours for heavy traffic areas

### WARNING

Do not apply product if air or surface temperature is below 55°F. Do not apply product in late afternoon or when rain or heavy dew is eminent.

### V.O.C.

The maximum V.O.C. of this product does not exceed 50 grams per liter.

### COMPLIANCE COATING

Meets SCAQMD-RULE 113

### THINNING

Small amount of Water if required for ease of application.  
DO NOT OVER THIN

### CLEAN-UP

Soap and warm water clean up.  
(A rinse with lacquer thinner, or brush cleaner may be necessary).

## SCOTCH PAINT CORPORATION

555 W. 189<sup>TH</sup> STREET

GARDENA, CA. 90248

800-404-2878