

Scotch Paint Corporation

· Paint Manufacturers and Distributors of Lacquers, Spray Equipment and Sundries ·

CORPORATE: 800-404-2878

555 West 189th Street Gardena, California 90248

FAX: 310-769-0436

PRODUCT NO. 325NR

DRAW-TITE NO RUN CLEAR

Description:

High performance penetrating sealer

Recommended Uses:

Drywall sealer
Wallpaper primer, sealer, sizing
Damaged drywall restorer
Penetrating sealer for porous surfaces

Applications:

One generous coat by
Airless sprayer
Hudson sprayer
Roller
Brush

Characteristics:

Finish: Semi gloss
Drying Time: 1-2 Hrs.
Spreading Rate: 300-600 Sq. feet/gallon
Volume Solids: 29.05%
Weight Solids: 30.16%
Weight/Gallon: 8.42 Lbs./gal
Heat Resistance: 140° F
Vehicle Type: Acrylic copolymer
Flash Point: N/A
Viscosity: Gel like consistency
V.O.C.: Less than 100 g/l

Thinning:

No thinning is required or recommended

Cleanup:

Clean spray equipment with water immediately
When finished

Surface Preparations:

For repair of torn or damaged drywall it is important to strip facing paper down to a sound layer or to the gypsum core if necessary, no product can jump air gaps in paper facing. Be sure all surfaces are dry, smooth and free from dirt, Grease wax and loose or checking paint. For best results when replacing existing wallpaper remove old wallpaper paste, Trace residue left after Washing wall is ok to cover.

Caution:

Observe ordinary precautions when using this product. Provide proper ventilation, avoid breathing vapors or spray mist and prolonged contact with skin. Wash hands before eating or smoking. DO NOT TAKE INTERNALLY, KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: DRAW-TITE NO RUN CLEAR
PRODUCT CODE: AQ-325NR

HMIS CODES: H F R P
1 0 0 X

=====**SECTION I - MANUFACTURER IDENTIFICATION**=====

MANUFACTURER'S NAME: Scotch Paint
ADDRESS: 555 WEST 189TH STREET, GARDENA, CALIFORNIA 90248
EMERGENCY PHONE: 310-329-1259 **INFORMATION PHONE:** 310-329-1259
DATE REVISED : 03-08-05 **NAME OF PREPARER :** RJN

=====**SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION**=====

HAZARDOUS COMPONENTS	OCCUPATIONAL EXPOSURE LIMITS				VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
	CAS NUMBER	OSHA PEL	ACGIH TLV	OTHER		
*ETHYLENE GLYCOL BUTYL ETHER	111-76-2	25ppm	25ppm		88.0 77F	3

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
FOLLOW ALL LABEL DIRECTIONS. WARNING THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR REPRODUCTIVE HARM. COMPLIES WITH TITLE 8 CALIFORNIA CODE OF REGULATIONS SECTION 5194.

=====**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**=====

BOILING POINT: 340 Deg F **SPECIFIC GRAVITY (H2O=1):** 1.0
VAPOR DENSITY: HEAVIER THAN AIR **EVAPORATION RATE:** SLOWER THAN ETHER
COATING V.O.C. : 0.75 LB/GL (90 G/L)
SOLUBILITY IN WATER: VEHICLE PORTION COMPLETE
APPEARANCE AND ODOR: SLIGHT AMMONIA

=====**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**=====

FLASH POINT: N/A **METHOD USED:** N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A **UPPER:** N/A

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

SELF CONTAINED BREATHING APPARATUS RECOMENDED. COMBUSTION PRODUCES CO,CO2

UNUSUAL FIRE AND EXPLOSION HAZARDS

=====
SECTION V - REACTIVITY DATA
=====**STABILITY: STABLE****CONDITIONS TO AVOID**

EXCESS HEAT, STRONG ACIDS OR ALKALIS

INCOMPATIBILITY (MATERIALS TO AVOID)

UNKNOWN

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

CO, CO2 ON COMBUSTION

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR=====
SECTION VI - HEALTH HAZARD DATA
=====**INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE**

NAUSEA, DIZZINESS, DROUSINESS, WEAKNESS, HEADACHE.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RASH, BURNING, SWELLING, ITCHING, WATERING EYES.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

RASH, SWELLING, ITCHING, REDNESS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

NAUSEA, CRAMPS, HEADACHE

HEALTH HAZARDS (ACUTE AND CHRONIC)

UNKNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

UNKNOWN

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

UNKNOWN

EMERGENCY AND FIRST AID PROCEDURES

INHALATION REMOVE TO FRESH AIR. IF UNCONSCIOUS CALL PHYSICIAN IMMEDIATELY.

INGESTION DO NOT INDUCE VOMITING CALL PH

YSICIAN IMMEDIATELY.

SKIN CONTACT WASH WELL WITH SOAP AND WATER. IF RASH DEVELOPES CONSULT PHYSICIAN

EYE CONTACT FLUSH WITH COPIOUS AMOUNT OF WATER CONSULT PHYSICIAN.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WIPE UP SMALL SPILLS WITH ABSORBANT RAGS OR TOWELS. LARGE SPILLS DIKE AREA AND PUMP INTO DRUMS FOR RECOVERY OR DISPOSAL

WASTE DISPOSAL METHOD

FOLLOW FEDERAL STATE AND LOCAL REGULATIONS REGARDING PROPER DISPOSAL OF PAINT AND RELATED MATERIALS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

WEAR APPROVED ORGANIC VAPOR RESPIRATOR UNLESS ADEQUATE VENTILATION EQUIPMENT IS AVAILABLE TO KEEP ORGANIC VAPOR BELOW TLV

OTHER PRECAUTIONS

KEEP CONTAINERS CLOSED WHEN NOT IN USE KEEP FROM OPEN FLAMES OR EXCESS HEAT STORE IN COOL DRY PLACES. DO NOT FREEZE
KEEP OUT OF REACH OF CHILDREN

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

WEAR APPROVED RESPIRATOR FOR DUST AND ORGANIC VAPORS.

VENTILATION

OPEN WINDOWS AND DOORS GENERALLY ARE SUFFICIENT TO KEEP TLV BELOW HAZARDOUS CONCENTRATIONS IF NOT EMPLOY MECHANICAL
VENTILATION EQUIPMENT TO KEEP BELOW TLV OF PRODUCT

PROTECTIVE GLOVES

USE NEOPRENE RUBBER GLOVES TO PROTECT AGAINST SKIN EXPOSURE

EYE PROTECTION

WEAR SPLASH RESISTANT GOGGLES TO PROTECT EYES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NEOPRENE RUBBER APRON RECOMMENDED WHEN USING THIS PRODUCT. WEAR HAT TO PROTECT SCALP FROM THIS PRODUCT.

WORK/HYGIENIC PRACTICES

EMERGENCY EYE WASH AND SAFETY SHOWERS RECOMMENDED. WASH HANDS BEFORE EATING OR SMOKING.

===== SECTION IX - DISCLAIMER =====

DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS FURNISHED WITHOUT WARRANTY OF ANY KIND INFORMATION FURNISHED IS BELIEVED TO BE
CORRECT. ANY USE OF THIS INFORMATION MUST BE VERIFIED BY INDEPENDENT DETERMINATION OF SUITABILITY AND COMPLETENESS.