

SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436

430 EASY GLIDE Semi-Gloss Enamel

DESCRIPTION

Easy Glide is a good quality maintenance Latex Semi-Gloss house and trim paint designed primarily for interior use. Recommended Uses: Drywall, wood, concrete, masonry, cured plaster and previously painted surfaces. For best results prime new work with an appropriate Scotch Primer, ask your expert dealer for their recommendations.

COLORS

White, and full range Tints

PACKAGING

Gallons, and 5 Gallon pails

FINISH

Semi-Gloss

Sheen 50 @ 60 degrees

SUBSTRATES

Properly primed wood, metal, and masonry.

DRYING TIME

To touch – 1-2 hour

To recoat – 4-6 hours

COVERAGE

250 to 350 sq. ft. per gallon

SURFACE PREPARATION

All surfaces must be clean and dry and free of dust, loose paint, and surface contaminants that may impair adhesion. Application in temperatures below 50^oF is not recommended.

SOLIDS BY VOLUME: 30%

V.O.C.

This product contains a maximum of 50 grams per liter.
Meets SCAQMD RULE 1113

APPLICATION

Airless or conventional spray, brush or roll.

PRIMER

BLOCK =

#S105 Block Filler
#330 Draw-Tite Primer

DRYWALL=

#320 PVA Sealer
#315 Latex Primer

TILT-UP or
BRICK =

#330 Draw-Tite Primer
#95 Busan Acrylic Primer

WOOD NEW =

#300 Bus-Stop 100% Acrylic Primer
#95 Busan Primer
#315 Latex Primer

PREVIOUSLY PAINTED =

#300 Bus-Stop 100% Acrylic Primer
#97 100% Acrylic Primer

METAL:
FERROUS =

#301 Red Oxide Primer
#302 White Primer

NON-FERROUS =

#302 White Primer
#300 Bus-Stop 100% Acrylic Primer
#97 100% Acrylic Primer
#95 Busan Primer or

THINNING

Small amount of Clean Water if required.

CLEAN-UP

Soap and warm water clean-up.

SCOTCH PAINT CORPORATION
555 W. 189TH STREET
GARDENA, CA. 90248