

SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436



7200 ACRY-SHEEN 100% Acrylic Satin Finish Enamel

DESCRIPTION

7200 ACRY-SHEEN is a quality satin enamel made with 100% acrylic resin. It has good durability on both exterior and interior surfaces. Use it on exterior sash & trim as well as kitchen and bathroom walls and cabinets and trim through out the home. Equally suitable for schools, hospitals and public buildings needing a durable satin finish. 7200 can also be manufactured special order as a ZERO V.O.C. coating.

COLORS

White, Stock Colors and Tints.
Factory Custom colors 100 gallon minimum.

PACKAGING

Quarts, gallons, 5 gallon pails

FINISH

Semi-Gloss

SUBSTRATES

Properly primed wood, metal, and masonry.

DRYING TIME

To touch - 1 hour
To recoat - 8 hours
Under normal weather conditions @70°F,
50 relative humidity

SOLIDS

By volume 37.08%

COVERAGE

350 to 450 sq. ft. per gallon

SURFACE PREPARATION

All surfaces must be clean and dry and free of dust, loose paint, and surface contaminants that may impair adhesion.

V.O.C. Does not exceed 50 grams/liter

APPLICATION

Airless or conventional spray, brush or roll.

PRIMER

BLOCK =	#S105 Block Filler
DRYWALL =	#PV101 PVA Sealer
	#7509 "F" Stop
TILT-UP or	#95 Busan Acrylic Primer
BRICK =	#330 Draw-Tite Primer
	#95 Busan Primer
WOOD,NEW =	#63 Dynacoat Enamel Undercoat (Interior only)
	#300 Bus-Stop 100% Acrylic Primer
	#97 100% Acrylic Primer
PREVIOUSLY PAINTED =	#902 Red Oxide Primer
	#905 Gray Primer
METAL:	
FERROUS =	#95 Busan Primer or
	#908 Zinc Phosphate
NON-FERROUS =	#300 Bus-Stop 100% Acrylic Primer
	#97 100% Acrylic Prime

THINNING

Small amount of Water if required.

CLEAN-UP Soap and warm water clean up.
(a rinse with lacquer thinner or brush cleaner may be necessary)

SCOTCH PAINT CORPORATION
555 W. 189TH STREET
GARDENA, CA. 90248