

SCOTCH PAINT CORPORATION

FACTORY: 800-404-2878

FAX: 310-769-0436



900 ACRILOX 100% Acrylic Floor Paint

DESCRIPTION

Scotch Acrilox is a superior 100% Acrylic floor paint for use on exterior and interior surfaces. Acrilox is an ideal product for concrete, masonry and properly prepared wood and metal surfaces. A non-skid additive may be added to this product for better traction.

COLORS

White, Stock Colors.
Full Color Spectrum of Tints Available From
Your Dealer.

PACKAGING

Quarts, gallons, (and 5 gallon pails on
selected stock colors and bases)

FINISH

Low-Luster

SUBSTRATES

Properly prepared concrete, masonry, wood,
and metal.

COVERAGE

250 to 450 sq. ft. per gallon, depending on
porosity and texture of surface. If non-skid
additive is mixed in, this will lessen your
coverage per sq. ft.

SURFACE PREPARATION

All surfaces must be clean and dry and
free of dust, loose paint, and surface
contaminants that may impair adhesion.
New concrete should cure for a minimum
of 60 days prior to painting. Smooth or
slick concrete should be acid etched, rinsed
and thoroughly dry to insure best adhesion.

APPLICATION

Airless or conventional spray, brush or roll. Apply two thin
coats rather than one heavy coat. For best results do not
apply to damp surfaces

DRYING TIME

1 Hour to touch
2 Hours recoat
Light foot traffic after 8 Hours
Let cure 24 to 36 Hours for heavy traffic areas

WARNING

Do not apply product if air or surface temperature is below
55°F. Do not apply product in late afternoon or when rain or
heavy dew is eminent.

V.O.C.

The maximum V.O.C. of this product does not exceed
50 grams per liter.

COMPLIANCE COATING

Meets SCAQMD-RULE 113

THINNING

Small amount of Water if required for ease of application.
DO NOT OVER THIN

CLEAN-UP

Soap and warm water clean up.
(A rinse with lacquer thinner, or brush cleaner
may be necessary).

SCOTCH PAINT CORPORATION

555 W. 189TH STREET
GARDENA, CA. 90248
800-404-2878