

Scotch Paint Corporation

• *Paint Manufacturers and Distributors of Lacquers, Spray Equipment and Sundries* •

CORPORATE: 1-800-404-2878

555 West 189th Street

Gardena, California 90248

FAX: 1-310-769-0436

PRODUCT NO. 300

BUS STOP

A 100% acrylic interior, exterior primer for surfaces that are prone to bleeding. Excellent primer for nearly all surfaces. L.A.U.S.D. approved.

• **RECOMMENDED USES:**

All Wood • Stucco • Hardboard • Plaster •
Masonry • Metal

• **CHARACTERISTICS:**

FINISH: White
DRYING TIME: 1-2 Hrs
SPREADING RATE: 300-400 Sq. feet per gallon
VOLUME SOLIDS: 42.31%
WEIGHT SOLIDS: 54.81%
WEIGHT / GALLON: 10.63
HEAT RESISTANCE: 125°
VEHICLE TYPE: 100% Acrylic
LIGHT REFLECTION: 80%
FLASH POINT: N / A
VISCOSITY: 95-100 KU

• **SURFACE PREPARATIONS:**

Make sure all surfaces are dry, smooth and free from dirt, grease, wax, and loose chalking paint.

• **APPLICATION:**

Use brush, roller, or spray equipment. Avoid painting in fog, mist, rain, or if the temperature is below 50° F.

• **THINNING:**

Not required. If thinning is desirable due to weather conditions, a small amount of water may be used.

• **CAUTION:**

Observe ordinary precautions when using this product. Wash hands before eating or smoking. Avoid breathing vapors or spray mist and prolonged contact with skin. Use only with adequate ventilation. **DO NOT TAKE INTERNALLY, KEEP FROM FREEZING AND KEEP OUT OF REACH OF CHILDREN.**