

Scotch Paint Corporation

• Paint Manufacturers and Distributors of Lacquers, Spray Equipment and Sundries •

CORPORATE: 1-800-404-2878

555 West 189th Street

Gardena, California 90248

FAX: 1-310-769-0436

PRODUCT NO. 445

ACRYLIC STAIN

An exterior vinyl acrylic solid color stain.

• RECOMMENDED USES:

Brick • Wood • Ceilings • Masonry •
Concrete Block

• CHARACTERISTICS:

FINISH: Flat
DRYING TIME: 1-2 Hrs
SPREADING RATE: 300-400 Sq. feet per gallon
VOLUME SOLIDS: 39.18%
WEIGHT SOLIDS: 56.39%
WEIGHT / GALLON: 11.61
HEAT RESISTANCE: 125° F
VEHICLE TYPE: Alkyd modified Vinyl
acrylic
LIGHT REFLECTION: 80%
FLASH POINT: N / A
VISCOSITY: 100-105 KU

• SURFACE PREPARATIONS:

Be sure all surfaces are dry, smooth and free from dirt, grease, wax, and loose chalking paint. Fill nail holes and cracks with spackling paste or putty. Always clean off all contamination between coats before applying subsequent coats. If surface to be coated is slick or shiny use sandpaper or liquid reglossing compound to remove the shine. Wipe thoroughly to be sure the surface is clean. **Concrete Block:** Fill with block fill. **Masonry:** New masonry shall be thoroughly dry and cured hard. For best results, use two coats. **Wood:** Apply one coat of latex undercoater alkyd wood primer. **Stucco:** For best

results, use two coats. **Brick:** For best results, use two coats. **Previously Painted Surfaces:** If in sound condition and uniform porosity, no primer is required. Remove dirt, grease, wax and any peeling or scaling paint. Clean surface contamination by washing with a powdered commercial cleaner. Rinse thoroughly and allow to dry. Dull gloss surface with fine sandpaper. Spot prime with appropriate primer.

• APPLICATION:

Use brush, roller, or spray equipment. Avoid painting in fog, mist, rain, or if the temperature is below 50° F.

• THINNING:

Not required. If thinning is desirable due to weather conditions, a small amount of water may be used.

• CAUTION:

Observe ordinary precautions when using this product. Wash hands before eating or smoking. Avoid breathing vapors or spray mist and prolonged contact with skin. Use only with adequate ventilation. DO NOT TAKE INTERNALLY, KEEP FROM FREEZING AND KEEP OUT OF REACH OF CHILDREN.