

# Scotch Paint Corporation

• *Paint Manufacturers and Distributors of Lacquers, Spray Equipment and Sundries* •

CORPORATE: 1-800-404-2878

555 West 189th Street

Gardena, California 90248

FAX: 1-310-769-0436

**PRODUCT NO. 465**

## DURASHEEN

A premium quality low lustre enamel. Manufactured with a vinyl acrylic blend for superior performance. Features outstanding washability and durability while providing a luxurious finish.

### • RECOMMENDED USES:

Drywall • Wood • Masonry • Concrete  
Hardboard • Primed Metal

### • CHARACTERISTICS:

FINISH:	Low lustre
DRYING TIME:	1-2 Hrs
SPREADING RATE:	350-450 Sq. feet per gallon
VOLUME SOLIDS:	39.58%
WEIGHT SOLIDS:	55.58%
WEIGHT / GALLON:	11.33
HEAT RESISTANCE:	125° F
VEHICLE TYPE:	Vinyl Acrylic Blend
FLASH POINT:	N / A
VISCOSITY:	95 KU
V.O.C.:	Less than 250 grams per liter

### • SURFACE PREPARATIONS:

Be sure all surfaces are dry, smooth and free from dirt, grease, wax, and loose chalking paint. Fill nail holes and cracks with spackling paste or putty. Always clean off all contamination between coats before applying subsequent coats. If surface to be coated is slick or shiny use sandpaper or liquid reglossing compound to remove the shine. Wipe thoroughly to be sure the surface is clean.

### • APPLICATION:

Use brush, roller, or spray equipment. Avoid painting in fog, mist, rain, or if the temperature is below 50° F.

### • THINNING:

Not required. If thinning is desirable due to weather conditions, a small amount of water may be used.

### • CAUTION:

Observe ordinary precautions when using this product. Wash hands before eating or smoking. Avoid breathing vapors or spray mist and prolonged contact with skin. Use only with adequate ventilation. **DO NOT TAKE INTERNALLY, KEEP FROM FREEZING AND KEEP OUT OF REACH OF CHILDREN.**